
Grinding-Polishing Machine GPM-240

LIGHT - PRODUCTIVE - RELIABLE - UNIVERSAL



Professional edging one-disc Grinding-Polishing Machine GPM-240 is used for grinding of uneven surfaces, polishing of concrete, terrazzo, stone, wooden surfaces on small areas. Can be used to remove old coverings, remains of glue, paint, etc. GPM-240 is convenient for operation at difficult-to-reach areas close to columns and edges, next to walls. The machine has **CE Declaration of Conformity**.

Model	Units	Working Condition	Transportation Condition	
Power	kW	1.5		
Parameters:	mm		Grinding Head	Control Panel
Length	mm	1310	535	1270
Width	mm	380	380	220
Height	mm	1140	370	295
Voltage	V	230		
Tools		and resin bond diamond tools, impregnated pads,		
	buffs,	tungsten-carbide segments, sandpaper pads, etc.		
Grinding disc diameter	mm	1x236		
Tool speed	rpm	100-2000		
Water tank capacity	1	2.5		
Weight, not more than	kg	39		
Price				



GENERAL FEATURES:

Operation close to the wall 0mm. Rollers on the skirt protect the wall from scratching




At close-to-wall operation easy to change from right to left side from the wall (and opposite) due to wheels axis movement



SPECIAL FEATURES FOR GPM-240:

- Regulation of tools rotation speed 100-2000rpm (inverter)
- Soft start and operation in three regimes due to changeable speed:
 - O Cleaning (floor washing with shampoo and water): 200-300rpm
 - o Grinding: 750-1000rpm
 - o Polishing: 1500-2000rpm

- Low weight of 39kg
- Small size









- ➤ Long life-time due to simple construction of the machine and all-metal parts
 - Reverse rotation of grinding disc change in tools rotation direction
- > Possibility to regulate pressure for grinding or polishing
- Control of tools levelness and flatness possibility to set tools in horizontal level





- Handle with regulated height and slope to ensure comfort operation
- Machine's handle protects control panel from mechanical damages

- ➤ Wet grinding or washing is possible due to regulated liquid supply from the water tank (2.5l) or regulated running water supply
- > Dust outlet for vacuum cleaner connection
- > Dust-free environment due to unique system of air swirl under the grinding head, outlet for vacuum cleaner connection and quick-detachable sliding rubber skirt on the grinding head
- Easily dismountable on two parts compact construction
- Light-colored strong aluminum wheels do not leave marks on floor
- Silent and convenient in operation
- Powerful projector lightning
- ➤ Wide choice of tools for different purposes
- Pocket for spare discs and tools

Stalats AB

P.O. Box 885 S-101 37 Stockholm Tel: +46700390087 E-Mail: info@stalats.com Web: www.stalats.com